

## **Amendments to the Claims**

This listing of claims will replace all prior versions and listings of claims in the application:

### Listing of Claims

Claim 1 (Currently Amended): A security enclosure for a control apparatus, said enclosure comprising:

a base;

a cage configured to connect to said base and encompass said apparatus;

a mounting member comprising:

a mounting shank embedded within said base; and

a mounting strap, having a strap width and a strap thickness, said mounting strap partially embedded within said base and joined to said mounting shank,  
~~and configured to extend inside said cage~~  
~~substantially perpendicular to said base when said cage is connected to said base;~~ and

a lock device configured to secure said cage to said mounting strap when said cage is connected to said base-;

wherein:

said cage has a strap engagement slot having a slot width greater than said strap width and a slot thickness greater than said strap thickness; and

said mounting strap is configured to extend inside said cage substantially vertically and perpendicular to said base through said strap engagement slot when said cage is connected to said base.

Claim 2 (Cancelled): .

Claim 3 (Withdrawn): An enclosure as claimed in claim 1  
wherein:

said mounting strap is a first mounting strap;

said lock device is a first lock device; and

said enclosure additionally comprises:

a second mounting strap configured to extend inside said  
cage substantially perpendicular to said base when  
said cage is connected to said base; and

a second lock device configured to secure said cage to  
said second mounting strap when said cage is  
connected to said base.

Claim 4-6 (Cancelled): .

Claim 7 (Previously Presented): An enclosure as claimed in  
claim ~~6~~1 wherein:

said cage has a cage lock hole and comprises a fixed lock tab  
having a tab hole;

said mounting strap has a strap lock hole; and

said lock device is configured to reside within said cage and  
strap lock holes when said cage is connected to said base, and  
~~said lock device~~ comprises a lock rod and a movable lock tab  
having a tab hole;

~~said cage comprises a fixed lock tab having a tab hole; and~~

said lock rod is configured to reside within said cage and  
strap lock holes with said fixed and movable tab holes  
substantially in alignment when said cage is connected to said  
base.

Claims 8-13 (Cancelled): .

Claim 14 (Original): An enclosure as claimed in claim 1  
wherein:

said lock device comprises:

a movable lock tab; and  
a lock rod; and

said enclosure additionally comprises:  
a fixed lock tab coupled to said cage;  
a shroud configured to enshroud said fixed and movable lock tabs  
when said cage is connected to said base.

Claim 15 (Previously Presented): A security enclosure for a  
control apparatus, said enclosure comprising:

a base;  
a cage configured to connect to said base and encompass said  
apparatus;  
a mounting member comprising:  
a pair of mounting straps, wherein each of said mounting  
straps is partially embedded within said base and has  
a strap lock hole; and  
a mounting shank embedded within said base, and extending  
between and joined to each of said mounting straps;  
a fixed lock tab affixed to said cage and having a tab hole;  
a lock device comprising:  
a movable lock tab having a tab hole; and  
a lock rod coupled to said movable lock tab; and  
a shroud configured to enshroud, in conjunction with said  
base, said fixed lock tab, said movable lock tab, and a lock  
having a shackle passing through said tab holes of said fixed and  
movable lock tabs when said cage is connected to said base.

Claim 16 (Previously Presented): An enclosure as claimed in  
claim 15 wherein:

said enclosure additionally comprises a lock plate coupled to  
said cage and having a cage lock hole;

each of said mounting straps is partially embedded within  
said base and configured to extend inside said cage substantially  
perpendicular to said base so that said strap lock hole

substantially aligns with said cage lock hole when said cage is connected to said base; and

said lock rod is configured to reside within said cage and strap lock holes when said cage is connected to said base.

Claim 17 (Original): An enclosure as claimed in claim 16 wherein:

said shroud is coupled to said lock plate;

said shroud enshrouds said fixed lock tab, said movable lock tab, and said lock upon three sides; and

said base enshrouds said fixed lock tab, said movable lock tab, and said lock upon a fourth side.

Claim 18 (Previously Presented): An enclosure as claimed in claim 15 wherein:

each of said mounting straps is partially embedded within said base and configured to extend inside said cage substantially perpendicular to said base when said cage is connected to said base; and

said lock rod is configured to couple said cage to each of said mounting straps.

Claim 19 (Previously Presented): An enclosure as claimed in claim 18 wherein:

a first one of said pair of mounting straps has a first strap lock hole;

a second one of said pair of mounting straps has a second strap lock hole substantially aligned with said first strap lock hole;

said cage comprises a first lock plate having a first cage lock hole;

said cage additionally comprises a second lock plate having a second cage lock hole substantially aligned with said first cage lock hole and, when said cage is connected to said base,

substantially aligned with said first and second strap lock holes; and

said lock rod is configured to reside in said first and second cage lock holes and said first and second strap lock holes when said cage is connected to said base.

Claim 20 (Previously Presented): A security enclosure for a fluid-control apparatus, said enclosure comprising:

a cage connected to a base and configured to encompass said apparatus, said cage comprising:

- a first "U" member;
- a second "U" member;
- a first angle member coupled between said first and second "U" members and having a first strap engagement slot;
- a second angle member coupled between said first and second "U" members and having a second strap engagement slot;
- a first lock plate coupled between said first and second "U" members and having a first cage lock hole;
- a second lock plate coupled between said first and second "U" members and having a second cage lock hole substantially aligned with said first cage lock hole
- a fixed lock tab proximate said first cage lock hole and having a tab hole;
- a first end panel coupled to said first "U" member;
- a second end panel coupled to said second "U" member;
- a perforated body panel coupled between said first and second "U" members; and
- a brace coupled between said first and second "U" members;

a mounting member comprising:

- a first mounting strap partially embedded within said base, configured to extend inside said cage

substantially perpendicular to said base through said first strap engagement slot, and having a first strap lock hole configured to substantially align with said first and second cage lock holes;

a second mounting strap partially embedded within said base, configured to extend inside said cage substantially perpendicular to said base through said second strap engagement slot, and having a second strap lock hole configured to substantially align with said first strap lock hole and with said first and second cage lock holes; and

a mounting shank embedded within said base and joined to said first and second mounting straps;

a lock device configured to secure said cage to said first and second mounting straps, said lock device comprising:

a movable lock tab having a tab hole; and

a lock rod coupled to said movable lock tab and configured to reside within said first cage lock hole, said first strap lock hole, said second strap lock hole, and said second cage lock hole so as to align said tab holes of said fixed and movable lock tabs; and

a shroud coupled to said first lock plate and configured to enshroud, in conjunction with said base, said fixed lock tab, said movable lock tab, and a lock having a shackle passing through said tab holes of said fixed and movable lock tabs.